

IMPORTANT INFORMATION



THIS TOWEL WARMER IS MADE OF MILD STEEL AND IS ONLY SUITABLE FOR USE ON CLOSED HEATING SYSTEMS WITH A CHEMICAL WATER TREATMENT INHIBITOR ADDED TO PROTECT AGAINST CORROSION, SCALE AND SLUDGE

FAILURE TO PROPERLY CLEANSE AND PROTECT THE SYSTEM WILL INVALIDATE THE WARRANTY AND IS LIKELY TO CAUSE SMALL PINHOLE LEAKS



Installation should be carried out by a qualified professional or other fully competent person and should be installed in accordance with the relevant British Standards (BS5449:1990, BS7593:1992, BSEN12828:2003 & BSEN12831:2003)

PLEASE READ THROUGH THE ENTIRE INSTALLATION INSTRUCTIONS BEFORE STARTING

Please check that all parts are present and that you are ENTIRELY happy with the size, design and finish of the product BEFORE starting installation.

We recommend the use of gloves, goggles and protective footwear when installing

PACK CONTENTS

1 x radiator	4 x bracket stems
4 x wall supports	4 x mini screws
4 x wall plugs	4 x washers
4 x wall screws	1 x chrome air vent plug
2 x decorative cover cap	

STEP 1

Screw the chrome blanking plug and chrome air vent plug, into the top two threads in the upright channels. They can be fitted on either side. Tighten firmly with a spanner, using a cloth to prevent scratching.



STEP 2

Screw the tails from the radiator valves (not supplied) into the bottom two threads using PTFE tape to seal. Wind the tape in the opposite direction to the thread.



STEP 3

Select your desired installation position and ensure that the wall is sufficiently strong enough to hold the weight of the radiator. Brick or breezeblock walls are ideal.

STEP 4

Screw the wall supports to the wall using the screw washers and wall plugs if you are mounting to brick or breezeblock.




STEP 5

Screw the bracket stems to the radiator and tighten firmly with spanner.




STEP 6

Ease the fixing brackets into wall support with the radiator. Push the radiator flat against the wall and tighten the 4 x mini screws to secure.




STEP 7

Connect the radiator valve tail to the radiator valve and tighten firmly.



STEP 8

Release any air trapped in the radiator using the air vent plug. When purging air from the system, carry a large cloth to catch the water while you are re-tightening the venting plug. Finally put decorative covers onto air vent and blanking plug



AFTER INSTALLATION THE CENTRAL HEATING SYSTEM MUST BE THOROUGHLY FLUSHED WITH A DOMESTIC WATER TREATMENT ASSOCIATION APPROVED CENTRAL HEATING PROTECTOR MUST BE ADDED TO THE SYSTEM.

Care and Maintenance

Central heating protector levels should be checked periodically in line with the manufacturer's recommendations.

Regular cleaning with a soft cloth will keep the surface of your towel warmer looking new.

Soapy water can be used to remove stubborn stains and then buff dry with a soft cloth.

Do not use abrasive or chemical cleaners to clean your towel warmer as these will damage the surface finish over time

These units can be installed so that the rail can be heated electrically when the central heating is switched off or just for stand alone electrical use with a dual fuel electrical element kit (sold separately). Please refer to the kit for installation instructions

FOR TECHNICAL SUPPORT DURING OR AFTER INSTALLATION PLEASE CALL 0845 644 6654

This towel rail is guaranteed to be free from defect caused by faulty materials or workmanship for a period of 1 year from date of purchase.

The guarantee is subject to the product being installed in accordance with British Standards (BS5449:1990, BS7593:1992, BSEN12828:2003 and BSEN12831:2003) as well as directed by the manufacturer in the installation instructions.

The manufacturer is not liable under this warranty for pinholes or defects caused by lack of a corrosion inhibitor (installation fault).

Our liability will under no circumstances extend beyond the repair or replacement of the product supplied by us. This warranty applies only to the United Kingdom.

Kudox Limited - 1 Bray Place SW3 3LL. London, United Kingdom